

MOVING TOWARDS GREEN MOBILITY



HIGHLIGHTS

ASIA STAR



DESIGN

Slick and futuristic design emphasizing technology and the future.

RANGE

Up to 200km in a single full charge.

SAFETY

Anti-Lock Braking System and Traction Control System to ensure passenger road safety.

INTERIOR

High quality interior fixings with generous seating and standing room to ensure passenger comfort.

ACCESSIBILITY

Low-entry with outward sliding door.

TECHNOLOGY

4 interior CCTV cameras to ensure an orderly journey for the passengers.

FOTON



DESIGN

Slick and futuristic design emphasizing technology and the future.

RANGE

Up to 270km in a single full charge.

SAFETY

Electric Braking System and Traction Control System to ensure passenger road safety.

INTERIOR

Generous seating and standing room to ensure passenger comfort.

ACCESSIBILITY

Low-entry with front and rear in-swinging anti-pinch door along with a manual wheelchair ramp.

TECHNOLOGY

8 interior CCTV cameras to ensure an orderly journey for the passengers.

VEHICLE SPECIFICATIONS

Asia Star



Dimensions & Weights

EXTERIOR DIMENSION (MM)

7,250 x 3,050 x 2,260

CURB WEIGHT (KG)

6,250

GROSS VEHICLE WEIGHT (KG)

9,800

WHEELBASE (MM)

4,460

SEATING CAPACITY

20 + 1

MAXIMUM CAPACITY

31 Passengers

Drive Train

MOTOR TYPE

Permanent Magnet
Synchronous Motor

MAXIMUM DRIVING RANGE (KM)

200

MAXIMUM POWER (KW) / TORQUE (N.M)

170 / 1,900

DRIVEN WHEEL

Rear Wheel Drive

Battery & Charging

BATTERY TYPE

Lithium Iron Phosphate

BATTERY CAPACITY (KWH)

127.7

CHARGING CONNETOR TYPE

CCS Type 2

Foton



Dimensions & Weight

EXTERIOR DIMENSION (MM)

8,450 x 3,150 x 2,435

CURB WEIGHT (KG)

9,600

GROSS VEHICLE WEIGHT (KG)

13,200

WHEELBASE (MM)

4,600

SEATING CAPACITY

20 + 2 + 1

MAXIMUM CAPACITY

37 Passengers

Drive Train

MOTOR TYPE

Permanent Magnet
Synchronous Motor

MAXIMUM DRIVING RANGE (KM)

270

MAXIMUM POWER (KW) / TORQUE (N.M)

145 / 2,100

DRIVEN WHEEL

Rear Wheel Drive

Battery & Charging

BATTERY TYPE

Lithium Iron Phosphate

BATTERY CAPACITY (KWH)

255.5

CHARGING CONNECTOR TYPE

CCS Type 2

Liannex Corporation Sdn Bhd

☎ Telephone | Fax numbers: 07-355 2244

📍 No.25, Jalan Firma 2, Kawasan Perindustrian Tebrau IV, 81100 Johor Bahru, Johor

✉ ryan.ng@liannex.com.my

